

HEART



Reliable Security for Every Door

DA1531

Crystal Series

Wall-mounted Access Controller / Reader

- can manage up to 1,000 access cards.
- Capable of managing up to 10 patrol cards.
- can store up to 1,500 event records temporarily.

Crystal Series- Wall-mounted Access Controller / Reader

Reliable Security for Every Door


Appearance Details Order Information



White
DA1531-A-W



Black
DA1531-A-B



General specifications


Characteristic	Specification	Description
Input Voltage	DC +10 ~ 15V	Stable low-voltage power input
Power Consumption	Max. 160mA @DC12V	Energy-efficient operation
Valid Card Capacity	Up to 1,000 cards	Card enrollment stops automatically when capacity is reached
Patrol Card Capacity	Up to 10 cards	Patrol-card swipes are recorded only; doors remain locked
Event Record Storage	Up to 1,500 records	Oldest records are automatically overwritten when full
Indicator Lights	Blue, Green, Red, White LEDs	Color indication corresponds to system status
Alarm Functions	Supported	Tamper alarm, forced-entry alarm, and door-open timeout alarm; configurable linkage with K2 alarm relay
Group Function	1 group	Independent holiday tables and time-zone schedules supported
Operating Temperature	0°C to 50°C	Reliable performance in indoor environments
Operating Humidity	5% to 95% RH	Non-condensing
Housing Material	ABS (UL94 V0)	Flame-retardant enclosure
Dimension (L x W x H)	120 x 72 x 24 mm	
Card Format	ISO/IEC 14443A	Reading distance up to 5 cm
Digital Inputs (DI)	3 sets	Exit button, door contact, emergency switch (NO/NC selectable)
Digital Outputs (DO)	2 sets	Door lock & alarm control (NO/NC selectable)
Built-in Battery	Rechargeable lithium battery	Maintains RTC up to 60 days power outage; auto-recharges when power is restored
Time-Based Access Control	Supported	7-day scheduling, up to 8 access time slots per day, holiday control, and historical record query
Remote Control Function	Supported	Host-command emergency door release for real-time unlocking via main controller

Crystal Series- Wall-mounted Access Controller / Reader


Reliable Security for Every Door

System Architecture

Multi-Door Access Control Product Series



User Interface



Product Features

- Patrol cards only record events without opening the door, ensuring patrols do not affect access security.
- Group management supports independent holiday and time-zone tables for flexible access rules.
- Equipped with a host-command emergency unlock function, enabling the host system to respond quickly to unexpected situations.
- Automatically overwrites records when full; card storage stops when full to prevent data overflow.
- After switching to offline mode, valid cards are verified locally to ensure operation during network interruptions.
- Weekly time zone control with 8 daily access periods, allowing multiple time zones per user and suitable for small to medium-sized facilities.
- Automatic time synchronization with the host computer.
- Utilizing an Ethernet communication interface, the dual ports enable automatic door unit detection or redundancy (backup) use.

