

HEART

Reliable Security for Every Door



DR1356

Crystal Series

Mifare Reader

- Reads ISO/IEC 14443A Format Cards
- Available in fingerprint card or MIFARE card reading models to meet different application needs
- Tamper output line and UL94V0 flame-retardant ABS housing

Crystal Series-Mifare Reader

Reliable Security for Every Door

Appearance Details



Supported Card Format (Optional):

- MIFARE Classic
- MIFARE Ultralight UID
- MIFARE DESFire EV1 UID
- MIFARE Classic Fingerprint Card

Order Information



DR1356-A-W

White



DR1356-A-B

Black



General specifications

Characteristic	Specification	Description
Input Voltage	DC +10 ~ 15V	Recommended linear regulator
Power Consumption	Max. 100 mA @ DC 12V	
Card Format	ISO/IEC 14443A	Reading distance up to 5 cm
Tamper output	Open collector, active low	Maximum Output Current: 100 mA
Transmission distance	When using 18 AWG shielded cable, the maximum transmission distance is 150 meters (500 feet).	
Indicator Lights	Blue, Green, Red LEDs	Indicator color changes with system status
Operating Temperature	0°C to 50°C	
Operating Humidity	5% to 95% RH	
Dimension(L x W x H)	120 x 72 x 24 mm	
Weight	150g max	
Housing Material	ABS(UL94V0)	
External control	Supported	Supports external control of light/buzzer

